

# PROXIMITY READERS AND KEYS

## PROXIMITY READERS (RFID)

MPROXUNI and MEDIPROXUNI, are multi-protocol proximity reader compatible with many other manufacture protocols as well as DELMAS's own 30 bit.

Characteristics common to both readers:

- multi-protocol
- proximity reader technology 125 KHz
- two-colour LED red and green + buzzer
- ABS box IP67
- resinate electronics
- 1 m cable

## MPROXUNI



**average reading distance, 3/6 cm**

### TECHNICAL SPECIFICATIONS

Power supply:	9 - 12 Vdc
Consumption:	20 mA
Operating temperature:	from -20°C to +55 °C
Protection rating:	IP 67
Dimensions and weight:	28 x 92 x 12 mm - 40 g.

## MEDIPROXUNI



**average reading distance 6/8 cm**

### TECHNICAL SPECIFICATIONS

Power supply:	9 - 12 Vdc
Consumption:	20 mA
Operating temperature:	from -20°C to +55 °C
Protection rating:	IP 67
Dimensions and weight:	43 x 80 x 13 mm - 70 g.

## KEYS FOR READERS



### BDGPROX

«Clamshell» shaped proximity badge,  
encrypted code DELMA IP67  
Dimensions and weight: 85x55x1 mm-20 g



### TAGPROX

Proximity tag with key  
holder encrypted DELMA, IP67.  
Dim. ø 35x55 mm